

## Polyfast Rodding

### PASTE GLUE FOR RODDING

Strong and fast paste glue specifically for rodding. Its flexibility, low shrinkage and high tightness make it ideal for under-top structural reinforcement (rodding).



**STRONG AND FAST BONDING**



**LOW WITHDRAWAL**



**EASILY DISPENSABLE**

#### Technical data:

- ◆ **Density at 25°C gr/cm<sup>3</sup>:** 0.98 / 0.96
- ◆ **Standard colour:** coloured
- ◆ **Appearance:** tending to yellow

#### Indicative consumption:

- ◆ **For grouting:**  
20-30MT linear
- ◆ **For bonding:**  
30-40MT2

The stated consumption is merely indicative



**Indoor  
Outdoor**



Natural stone



Quartz

#### How to apply it:

- ◆ Open the pack.
- ◆ Unscrew the transparent safety cap of the cartridge.
- ◆ Remove the second cap.
- ◆ Engage the mixer.
- ◆ Make sure the mixer is securely attached.
- ◆ Lock with the safety cap by screwing it in.
- ◆ Insert the cartridge into the specific gun 1:1.
- ◆ Discard the first 10 cm or so of the extruded product to align part A with part B (repeat this operation each time a mixer is changed).
- ◆ Extrude with constant and adequate pressure to ensure proper mixing of the two components and thus proper curing of the product.
- ◆ For proper curing of the product, it is necessary to purge and, if necessary, change the mixer between extrusions according to the instructions in the data sheet.
- ◆ After use, remove the mixer and close the cartridge with the safety cap.

#### Performance:

<b>Adhesion strength [Mpa]</b>	marble 8.0
<b>Gel time at 25°C</b>	4-7min
<b>Working time at 25°C</b>	25-30min
<b>Extraclear</b>	no
<b>Stability in sunlight</b>	low
<b>Wet adhesion</b>	low

#### Safety measures:

Read the instructions in the technical and safety data sheet and the notes on the packaging before use. Close the container after use. For professional use only.

#### Warnings:

When a surface is treated for the first time, it is advisable to evaluate the effect or adhesion on a sample or hidden corner.